



## DOUBLE ADJUSTABLE SHOCKS

The G3 shock is a mono - tube double adjustable shock available in 5" - 6" - 7" and 9" stroke and any possible valving or split valving.

The G3 has a fully anodized aluminum body with a large built-on gas reservoir. This increases the volume of gas the shock will hold, which lowers the unwanted increase in rod pressure that comes with stroke.

### Features

- Positive stainless steel no-drag scraper to keep any dirt and debris out.
- Hollow chrome-moly shaft.
- Low friction Teflon lined self lubricating 1/2 inch bearing on both ends.
- The finest High quality, High viscosity index shock absorber oils.
- Proprietary Dynamic Gas Pressure Control, keeps pressure low while supporting compression valve values.
- Double checked low-speed valving design.
- Completely independent rebound and compression adjustment.
- If more Extended length is needed as in a shock extension it **MUST** be ordered on shock when ordering.

Series	Extended Length	Compressed Length	Travel	Weight
G3 - 5"	15 3/4	11 1/4	4 1/2 inch	#2.8
G3 - 6"	17 3/4	12 1/4	5 1/2 inch	#3.0
G3 - 7"	19 3/4	13 1/4	6 1/2 inch	#3.2
G3 - 9"	24 3/4	15 3/4	9 inch	#3.6



5020 Old Ellis Point - Suite 200  
Roswell, Georgia 30076  
WWW.Genesishocks.com

678-659-9454  
Fax - 678-659-9457  
E-mail - info@Genesishocks.com



## **G<sup>2</sup> SERIES**

### **SINGLE ADJUSTABLE SHOCKS**

The G2 shock is a mono - tube single adjustable shock available in 5" - 6" - 7" and 9" stroke and any possible valving or split valving.

The G2 has a fully anodized aluminum body with a large built-on gas reservoir. This increases the volume of gas the shock will hold, which lowers the unwanted increase in rod pressure that comes with stroke.

#### **Features**

- Positive stainless steel no-drag scraper to keep any dirt and debris out.
- Hollow chrome-moly shaft.
- Low friction Teflon lined self lubricating 1/2 inch bearing on both ends.
- The finest High quality, High viscosity index shock absorber oils.
- Proprietary Dynamic Gas Pressure Control, keeps pressure low while supporting compression valve values.
- Double checked low-speed valving design.
- Completely independent rebound or compression adjustment.
- If more Extended length is needed as in a shock extension it **MUST** be ordered on shock when ordering.

Series	Extended Length	Compressed Length	Travel	Weight
G2 - 5"	15 3/4	11 1/4	4 1/2 inch	#2.8
G2 - 6"	17 3/4	12 1/4	5 1/2 inch	#3.0
G2 - 7"	19 3/4	13 1/4	6 1/2 inch	#3.2
G2 - 9"	24 3/4	15 3/4	9 inch	#3.6



**Can be ordered with either Rebound or Compression adjustment.**

5020 Old Ellis Point - Suite 200  
Roswell, Georgia 30076  
WWW.Genesisshocks.com

678-659-9454  
Fax - 678-659-9457  
E-mail - info@Genesisshocks.com